





Model No.	BİRİM	ÇEVİRİM (TAHVİL)	#50	#70	#90	#120	#145	#180	#220
NOMİNAL ÇIKIŞ TORKU	Nm	3	17	50	125	268	482	940	1420
		4	15	45	111	238	426	860	1300
		5	14	42	104	223	401	835	1270
		7	13	39	98	208	373	790	1180
		10	12	37	92	198	356	760	1140
MAX. ÇIKIŞ TORKU	Nm	3~10	3 x NOMİNAL ÇIKIŞ TORKU						
NOMİNAL GİRİŞ DEVRİ	rpm	3~10	5,000	4,800	4,000	3,600	3,000	3,000	3,000
MAX GİRİŞ DEVRİ	rpm	3~10	8,000	6,000	6,000	4,800	3,600	3,600	3,600
BOŞLUK ORANI	arcmin	3~10	≤8	≤8	≤8	≤8	≤8	≤8	≤8
BURULMA DİRENCİ	Nm/arcmin	3~10	2.3	5	15	45	69	140	220
MAX. RADYAL YÜK	N	3~10	750	1,180	3,000	6,500	9,100	11,150	35,000
MAX. AKSİYAL YÜK	N	3~10	325	590	1,500	3,250	4,550	5,575	17,500
HİZMET ÖMRÜ	hr	3~10	20,000						
VERİM	%	3~10	≥97%						
ÇALIŞMA SICAKLIĞI	°C	3~10	-25°C ~ +90°C						
YAĞLAMA		3~10	SENTETİK YAĞ						
REDÜKTÖR KORUMA DERESESİ		3~10	IP65						
MONTAJ POZİSYONU		3~10	HER YÖNDE						
SES SEVİYESİ	dB	3~10	≤62	≤62	≤65	≤68	≤70	≤70	≤70
AĞIRLIK ± 3%	Kg	3~10	0.63	1.57	3.22	8	16		

